

Pump Packages Continued



Pump Package 3 | Concentrated Acids & Alkalis

Engineered to transfer very concentrated and extremely aggressive liquids. Common applications include: Sulfuric Acid 66 Baumé, Propionic Acid, Concentrated Nitric (98%) and Hydrofluoric Acid.

Motor Type:	SP-ENC-V or SP-ENC-2-V
Pump Assembly:	PVDF (Kynar®)
Pump Length:	39" (1000 mm) or 47" (1200 mm)
Hose:	1,8m, I.D. 1" (25 mm) Atex/Chem. hose
Dispensing Nozzle:	1" (25 mm), PVDF
Barrel Adapter:	Polypropylene
Storage Bracket:	Steel
Max. Flow Rate:	66 LPM based on water
Max. Pressure:	10,6 m
Max. Viscosity:	1500 cps (mPas)
Max. Temperature:	80° C

PART NUMBER:

39" (1000 mm) Pump Length
9420 110-120V Package
9421A 220-240V Package
47" (1200 mm) Pump Length
9422 110-120V Package
9423A 220-240V Package



Pump Package 4 | Acids & Alkalis Measurement

Unique design allows users to safely measure and transfer corrosive liquids. Common applications include: Hydrochloric Acid, Nitric Acid (20%), Acetic Acid and Sulfuric Acid.

Motor Type:	SP-280P-V or SP-280P-2-V
Pump Assembly:	Polypropylene
Pump Length:	39" (1000 mm) or 47" (1200 mm)
Hose:	1,8 m, I.D. 1" (25 mm) PVC
Dispensing Nozzle:	1" (25 mm), Polypropylene
Flow Meter:	Digital / Polypropylene Totalizer
Barrel Adapter:	Polypropylene
Storage Bracket:	Steel
Max. Flow Rate:	51 LPM based on water
Max. Viscosity:	300 cps (mPas)
Max. Temperature:	55° C

PART NUMBER:

39" (1000 mm) Pump Length
9500 110-120V Package
9501 220-240V Package
47" (1200 mm) Pump Length
9502 110-120V Package
9503 220-240V Package



Pump Package 5 | Concentrated Acids & Alkalis Measurement

Unique design allows operators to safely measure and transfer concentrated and very aggressive liquids. Common applications include: Sulfuric Acid 66 Baumé, Propionic Acid, Concentrated Nitric (98%) and Hydrofluoric Acid.

Motor Type:	SP-ENC-V or SP-ENC-2-V
Pump Assembly:	PVDF (Kynar®)
Pump Length:	39" (1000 mm) or 47" (1200 mm)
Hose:	1,8m, I.D. 1" (25 mm) Atex/Chem. hose
Dispensing Nozzle:	1" (25 mm), PVDF
Flow Meter:	Digital / PVDF Totalizer
Barrel Adapter:	Polypropylene
Storage Bracket:	Steel
Max. Flow Rate:	61 LPM based on water
Max. Viscosity:	300 cps (mPas)
Max. Temperature:	80° C

PART NUMBER:

39" (1000 mm) Pump Length
9510 110-120V Package
9511 220-240V Package
47" (1200 mm) Pump Length
9512 110-120V Package
9513 220-240V Package

Pump packages with SPE-450 motors available on request