

Pump Packages Continued



Pump Package 9 | Flammable & Combustible Liquids

Explosion Proof Drum Pump is a safe solution for transferring highly flammable/combustible liquids and meets the stringent safety requirements of the Chemical Processing Industry. Applications include: Alcohol, Isopropyl Ether, Gasoline, Solvents, Aqueous Ammonia, Petroleum Products, Xylene, Toluene.

Motor Type:	SP-420EX (IP 54)
Pump Assembly:	SS316
Pump Length:	39" (1000 mm) or 47" (1200 mm)
Hose:	1,8m, I.D. 1" (25 mm) AtEx/Chem. Hose
Dispensing Nozzle:	1" (25mm) SS316
Barrel Adapter:	Stainless Steel
Storage Bracket:	Steel
Max. Flow Rate:	68 lpm based on water
Max. Viscosity:	750 cps (mPas)
Max. Temperature:	AtEx: 40° C (non-AtEx environment: 80° C)

PART NUMBER:

<u>39" (1000mm) Pump Length</u>	
9610	110-120V Package 
9611	220-240V Package 
<u>47" (1200 mm) Pump Length</u>	
9612	110-120V Package 
9613	220-240V Package 



Pump Package SPEK-ALU-ATEX Non-corrosive liquids and light oils

Standard Pumps Explosion Proof Drum Pump is designed safely transfer highly flammable/combustible liquids and meets the stringent safety requirements of the Chemical Processing Industry. Common applications include: Alcohol, Isopropyl Ether, Aqueous Ammonia, Xylene, Gasoline, Solvents, Petroleum Products and Toluene.

Motor Type:	EXP (IP54)
Pump Assembly:	AL
Pump Length:	39" (1000 mm) or 47" (1200 mm)
Hose:	1,8m, I.D. 1" (25 mm) AtEx Hose
Dispensing Nozzle:	1" (25mm), Aluminium
Barrel Adapter:	Aluminium
Storage Bracket:	Stainless Steel
Max. Flow Rate:	83 LPM based on water
Max. Pressure:	10,6 m
Max. Viscosity:	750 cps (mPas)
Max. Temperature:	40° C

PART NUMBER:

<u>SPEK-ALU-ATEX-39 220V - 240V</u>	
39" (1000 mm) Pump Length	
<u>SPEK-ALU-ATEX-47 220V - 240V</u>	
47" (1200 mm) Pump Length	



Pump Package SPEK-ALU-ATEX-AIR Non-corrosive liquids and light oils

Standard Pumps Proof Drum Pump (AIR) is designed safely transfer highly flammable/combustible liquids and meets the stringent safety requirements of the Chemical Processing Industry. Common applications include: Alcohol, Isopropyl Ether, Aqueous Ammonia, Xylene, Gasoline, Solvents, Petroleum Products and Toluene.

Motor Type:	SP-A1
Pump Assembly:	AL
Pump Length:	39" (1000 mm) or 47" (1200 mm)
Hose:	1,8m, I.D. 1" (25 mm) AtEx Hose
Dispensing Nozzle:	1" (25mm), Aluminium
Barrel Adapter:	Aluminium
Storage Bracket:	Stainless Steel
Max. Flow Rate:	83 LPM based on water
Max. Pressure:	10,6 m
Max. Viscosity:	450 cps (mPas)
Max. Temperature:	40° C

PART NUMBER:

<u>SPEK-ALU-ATEX-AIR 39 220V - 240V</u>	
39" (1000 mm) Pump Length	
<u>SPEK-ALU-ATEX-AIR 47 220V - 240V</u>	
47" (1200 mm) Pump Length	